

Paragraph at page 13, line 27, to page 13, line 28:

~~AB~~ Silicone, alumina, partially-stabilized-zirconia, or the like, can be used as the flexible base material 2.

**In the Claims:**

Please amend claims 1, 2, 7, 12, 13, 16, 17, 19 and 20 pursuant to 37 C.F.R. § 1.121(c)(1)(i) as set forth in the "clean" version set forth below. Entry is respectfully requested. A version with markings to show the changes made pursuant to 37 C.F.R. § 1.121(c)(1)(ii) is attached hereto as Appendix A.

~~Sub 1~~  
1. (Amended) A heat controller for an object comprising:  
a composite material comprising:  
a base material radiating a large amount of heat at a high-temperature phase; and  
a phase-change substance overlying said base material having insulation properties at a high-temperature phase, metallic properties at a low-temperature phase, radiating a large amount of heat at a high-temperature phase, radiating a small amount of heat at a low-temperature phase, and having a high reflectivity in the thermal infrared light region at a low-temperature phase.

A7  
2. (Amended) A heat controller according to claim 1, wherein said phase-change substance comprises a thickness in the range from about one to about thirty microns.

AS  
7. (Amended) A heat controller according to claim 1, wherein said base material is selected from a group consisting of silicone, alumina, and partially stabilized-zirconia.

A9  
12. (Amended) A heat controller according to claim 1, wherein said object includes an electronic circuit used in a space vehicle, including a man-made satellite and a spaceship.

13. (Amended) A method for controlling heat in an object comprising:  
providing a composite material on said object, said composite material formed of a base material radiating a large amount of heat at a high-temperature phase; and  
providing a phase-change substance on said base material having insulation properties at a high-temperature phase, metallic properties at a low-temperature phase, radiating a large amount of heat at a high-temperature phase, radiating a small amount of heat at a low-temperature phase, and having a high reflectivity in the thermal infrared region at a low-temperature phase.

17. (Amended) A method for controlling heat according to claim 13, wherein said base material is selected from a group consisting of silicone, alumina and partially stabilized-zirconia.

19. (Amended) A method for controlling heat according to claim 13, wherein said composite material is affixed to a surface of said object, either directly or via an intervening heat-conductive substance.

20. (Amended) A method for controlling heat according to claim 13, wherein said object includes an electronic circuit used in a space vehicle, including a man-made satellite and a spaceship.